

EXHIBIT H

COMPARISON OF APPLICATION '047 CLAIM 17 WITH THE PROPOSED COUNT

<u>Proposed Count</u>	<u>Application Claim</u>
<p>A pet carrier/portable structure for transporting and or confining animals comprising:</p> <p>a bottom floor panel and a roof panel,</p> <p>first and second side panels hingedly connected to said bottom panel and to said roof panel, said first and second side panels having external surfaces and upper and lower hingedly connected sections which allow the external surfaces of the wall panels to define an angle less than or equal 180 degrees and an angle greater than 180 degrees relative to one another,</p> <p>a pair of endwalls which are hingedly attached to the floor panel which endwalls retain the external surfaces of the wall panels at an angle greater than 180 degrees relative to one another.</p>	<p>17. A collapsible pet housing structure comprising:</p> <p>a floor panel having a pair of parallel sides and a pair of ends extending between the sides;</p> <p>a pair of generally opposing walls hingedly attached to the parallel sides of the floor panel, each of the walls comprising at least two generally planar wall panels hingedly connected to one another along a hinge line, each of the wall panels having an external surface and an internal surface, the internal surface of the wall panels of one wall facing the internal surface of the wall panels of the opposing wall, the hinged connection between the wall panels allowing the wall panels to cooperate with one another to retain the external surfaces of the wall panels at an angle greater than 180 degrees relative to one another, so that the hinged connection allows movement of the wall panels from:</p> <p>a first position where the external surfaces of the wall panels are at an acute angle relative to one another</p> <p>to a second position where the external surfaces of the wall panels are retained at an angle greater than 180 degrees relative to one another by a pair of endwalls,</p> <p>each endwall being hingedly attached to said floor panel at opposing ends of the floor panel, the endwalls pivoting from a</p>

	<p>position where both endwalls lie over said floor panel to a generally normal position with said floor panel to cooperate with said wall panels when said wall panels are in said second position to retain the external surfaces of the wall panels at the second position relative to one another; and</p> <p>a roof panel, the roof panel being of a weight and extending between the walls and being hingedly connected to said walls, so that the roof panel is at least partially supported by said walls when said wall panels are at the second position relative to one another, so that the roof panel cooperates with the wall panels and the endwalls to maintain the wall panels in the second position.</p>
--	---